

# Neo Primer

## MATERIAL SAFETY DATA SHEET

The information contained within this MSDS details health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user of this product should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Waterproofing Systems Ltd. Waterproofing Systems Ltd makes no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely, and to comply with all relevant legislation. Waterproofing Systems Ltd shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendation or information contained herein, from abnormal use of the material, or any hazard inherent in the nature of the material.

### COMPANY DETAILS

Company	Waterproofing Systems Ltd
Address	PO Box 1113, Palmerston North, New Zealand
Telephone	+64 6 357 9148
Facsimile	+64 6 357 9410
Email	info@waterproofing.co.nz

### IDENTIFICATION

Product Name	Neo Primer
Other Names	None.
Manufacturer's Product Code	Neo Primer.

### EMERGENCY AND FIRST AID PROCEDURES

Eye Contact	<ul style="list-style-type: none"><li>Hold eyelids open and flush immediately with gentle stream of water for at least 15 minutes, preferably at eyewash fountain</li><li>Get medical attention</li></ul>
Skin Contact	<ul style="list-style-type: none"><li>Clean by washing affected area with soap and water</li></ul>
Inhalation	<ul style="list-style-type: none"><li>If a person has subjective symptoms, they should be moved to a fresh air area. If pain and irritation develop, call a physician for examination and treatment as soon as possible.</li></ul>
Ingestion	<ul style="list-style-type: none"><li>Vomit and wash in case of swallowing without delay. In case of sticking to a mucous membrane of the skin, washout without delay.</li></ul>

### FIRE FIGHTING MEASURES

Flash Point	4°C
Fire-fighting Equipment	<ul style="list-style-type: none"><li>Wear full bunker gear including a positive pressure self-contained breathing apparatus in any closed space.</li><li>Use dry chemical foam, CO2</li><li>Protect against inhalation of toluene vapours and other decomposition/combustion products.</li></ul>

### ACCIDENTAL RELEASE MEASURES

Contain and cover it with inert materials dry sand, sawdust and cloth. It will become hard on account of reacting to moisture in air

### HANDLING AND STORAGE

#### HANDLING

Engineering Controls	The use of local exhaust ventilations is recommended to control processing emissions near the source
Respiratory Protection	Use a Gas Mask
Protective Clothing	Wear protective gloves, clothing and footwear to prevent skin contact
Eye Protection	Use Safety Glasses
Other Protective Devices	Safety shower and eye wash station near work area

#### STORAGE

Store in a cool, well ventilated place away from incompatible materials

#### PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Black, Liquid
Specific Gravity	0.88
Solubility in water	Negligible
Odour	A little
Boiling Point	110.6°C (Toluene), 80-128°C (industrial gasoline)

#### STABILITY AND REACTIVITY

Stable under/at normal conditions.

#### TOXIC HAZARDOUS INFORMATION

Acute Toxicity	Rat LD60 5000mg/kg(Toluene)
Chronic Toxicity	Toluene and normal hexane have possibility to damage a human body

#### ENVIRONMENTAL IMPACT

Toxicity to fishes: Especially normal hexane is said to affect fin.

Do not cast off in the environment: Sewer, River and Pond.

#### DISPOSAL CAUTION

Any disposal practice must be in compliance with local state and federal laws and regulations

#### TRANSPORTATION CAUTION

FIRE BAN. Do not fall, drop or damage.

#### CONTACT POINT

Waterproofing Systems Ltd Technical Department	06 357 9148
National Poisons Information Centre	0800 764 766
Police & Fire Brigade	111